

American Standard

 **BARRIER FREE**

AFWALL™ ELONGATED 1.6 GPF FLUSHOMETER TOILET

AFWALL™ ELONGATED TOILET

- Wall-mounted flushometer valve toilet
- Vitreous china
- Low-consumption (6.0 Lpf/1.6 gpf)
- EverClean™ anti-microbial surface which inhibits the growth of stain and odor causing bacteria, mold, and mildew
- Condensation channel
- Elongated bowl
- Powerful direct-fed siphon jet action
- 1-1/2" inlet spud
- Fully-glazed 2-1/8" trapway
- 10" x 12" water surface area
- 100% factory flush tested

- 3351.160** Elongated bowl only, top spud
- 3352.160** Elongated bowl only, top spud with slotted rim for bedpan holding (White only)
- 3353.160** Elongated bowl only, back spud
- 3354.160** Elongated bowl only, back spud with slotted rim for bedpan holding (White only)

Component Parts:

- 047007-0070A** Inlet Spud (furnished with bowl)

Nominal Dimensions:

660 x 356 x 381mm
(26" x 14" x 15")

Recommended working pressure—between
25 psi at valve when flushing and 80 psi static

Fixture only, less seat, bolt caps, and flush valve

Compliance Certifications -

Meets or Exceeds the Following Specifications:

- ASME A112.19.2 for Vitreous China Fixtures
- CAN/CSA International B45



SEE REVERSE FOR ROUGHING-IN DIMENSIONS

To Be Specified:

- Color: White Bone Silver Linen
- Seat:
 - American Standard #5901.100 Heavy duty open front less cover
 - American Standard #5905.100 Extra heavy duty open front less cover
- Alternative Seat:
 - Olsonite #95 open front seat less cover
 - Church #9500C open front seat less cover
- Flushometer Valve:
 - American Standard Selectronic™ #6065.161.002 (Top Spud) Available Nov. 1, 2007
 - American Standard Selectronic™ #6065.262.007 (Concealed Back Spud) Available Nov. 1, 2007
- Alternative Flushometer Valve:
 - Sloan Royal #111 (Top Spud)
 - Sloan Royal #144-1.5 (Back Spud)



MEETS THE AMERICANS WITH DISABILITIES ACT GUIDELINES
AND ANSI A117.1 REQUIREMENTS FOR ACCESSIBLE AND USABLE
BUILDING FACILITIES - CHECK LOCAL CODES.

- When installed so top of seat is 432 to 483mm (17" to 19") from the finished floor.

